

SCAP/SNCPS Cover Caps / Socket Head Cap Screws for Cover Caps









Corrosion resistance changes depending on use conditions. Always carry out tests under conditions same as actual conditions before use.

SNCPS

SCAP-AL Cover Caps : Aluminum Alloy (A5056)

SCAP-AL Cover Caps : Aluminum Alloy (A5056) Unit : mm											
Part Number	Μ	н	Dı	h	a	ta	Recommendation Torque (N•m)	SNCPS Part.No	Mass (g)	Qty per pack	
SCAP-3-AL	M5×0.5	5	7	2	0.8	0.6	0.1	SNCPS-M3	0.4	1	
SCAP-4-AL	M6×0.75	7	8	2.8	1.2	1	0.15	SNCPS-M4	0.6	1	
SCAP-5-AL	M8×0.75	8	10	3.5	1.2	1	0.3	SNCPS-M5	1	1	
SCAP-6-AL	M10×0.75	9	12	4	1.6	1.2	0.4	SNCPS-M6	1.5	1	
SCAP-8-AL	M12×1	11	14	5	2	1.8	0.6	SNCPS-M8	2.3	1	
SCAP-10-AL	M16×1	12	18	6	2.5	2	0.8	SNCPS-M10	3.7	1	

SCAP-CE	Cover	Caps : Cer	amic (Al ₂ O ₃)	

Part Number	Μ	н	D1	h	В	tB	Recommendation Torque (N•m)	SNCPS Part.No	Mass (g)	Qty per pack
SCAP-3-CE	M5×0.5	6	9	2	7	3	0.1	SNCPS-M3	1.2	1
SCAP-4-CE	M6×0.75	8	10	2.8	8	3	0.15	SNCPS-M4	2	1
SCAP-5-CE	M8×0.75	9	12	3.5	9	3	0.3	SNCPS-M5	3	1
SCAP-6-CE	M10×0.75	10	14	4	11	4	0.4	SNCPS-M6	4.3	1
SCAP-8-CE	M12×1	11	16	5	13	4	0.6	SNCPS-M8	5.8	1
SCAP-10-CE	M16×1	12	20	6	17	4	0.8	SNCPS-M10	9.2	1

👖 Individual Sales 🗕 P.794 ≪ Cleanroom Wash & Packaging 🗕 P.792 🚛 Screw Length Adjustment 🔶 P.796 💶 Vibration Resistant 🔶 P.795 ដ Modification process for captive use 🗕 P.791 1 pc. in 1 bag

Cleanroom washed and packed S.S. only/ Add'l charge Male screw only/ Add'l charge Not Available







- Combine **SCAP** Cover Cap and **SNCPS** Socket Head Cap Screw for Cover Cap.
- These caps prevent the corrosion of screw heads due to vacuum chamber processing gas and plasma.
- **SCAP** has 2 material types as standard. SCAP-AL -Aluminum alloy SCAP-CE -Ceramic
- The screw connection section is made of stainless steel, so this product has a higher tightening
- strength than aluminum or ceramic screws. • Other requested materials such as Inconel* and Hastelloy* can be used for Cover Caps.

*Inconel is a registered trademark of Special Metals Corporation. *Hastelloy is a registered trademark of Haynes International, Inc.

Application


Film formation equipment, etching devices, FPD production equipment, and semiconductor devices

Material/Finish										
	SCAP-AL Cover Caps	SCAP-CE Cover Caps	SNCPS Cap Screws							
Main Body	A5056	Al2O3 (99.5% Alumina)	SUSXM7 (S.S. grade : A2)							
Strength Class			A2-50							

Unit:mm

Usage

After tightening **SNCPS** Socket Head Cap Screw for Cover Cap, assemble **SCAP** Cover Cap so that it covers the head of **SNCPS**. Ensure that the tightening torque of **SCAP** does not exceed the recommendation torque in the chart.



Unit:mm

SNCPS Socket Head Cap Screw for Cover Cap

Part Number	м	L 📢										M1	L1	в	t	L2*1	SCAP Part.No	Mass (g)
SNCPS-M3	M3	6	8	10	12							M5×0.5	2	2	1.5	Full Thread	SCAP-3	0.53 - 0.78
SNCPS-M4	M4		8	10	12	16						M6×0.75	2.8	2.5	2.3	Full Thread	SCAP-4	1.3 - 1.9
SNCPS-M5	M5			10	12	16	20					M8×0.75	3.5	3	2.7	Full Thread	SCAP-5	2 - 3.3
SNCPS-M6	M6				12	16	20	25				M10×0.75	4	4	3	Full Thread	SCAP-6	3.8 - 6.4
SNCPS-M8	M8					16	20	25	30	35		M12×1	5	5	3.8	22(L=35)	SCAP-8	9 - 16
SNCPS-M10	M10						20	25	30	35	40	M16×1	6	6	4.5	26(L=40)	SCAP-10	17 - 27

*1 If the "L" value is other than the value in parentheses, the screw is full thread.

Part Number	Qty per pack
SNCPS-M3	1
SNCPS-M4	1
SNCPS-M5	1
SNCPS-M6	1
SNCPS-M8	1
SNCPS-M10	1

