

# SNF-SD / SNFS-SD

Cross Recessed Flat Head Machine Screws with Small Head




WEB Selection Tool

WEB CAD Download

Small Head

SUS Stainless steel



● Part number specification

## SNF - M5 - 20 - SD - TZB



Order in number of packs.  
The minimum order quantity is 1 piece. → P.794

- Cross Recessed flat head machine screws with small head diameters. This makes it possible to reduce the spot facing diameters compared to standard flat head machine screws.
- Since the head height is lower than that of standard flat head screws. Suitable for connecting thin plates.

● Application

Reducing the size of equipment and devices

● Material/Finish 1

RoHS Compliant

	SNF-SD-TZB	SNFS-SD
Main Body	SWCH Trivalent Chromate Treatment	SUSXM7 (S.S. grade : A2)

Unit : mm

SNF-SD-TZB Steel - Trivalent Chromate Treatment	SNFS-SD Stainless steel	Common dimensions												
Part Number	Part Number	M	L								D1	L1	Mass (g)	
SNF-M3-SD-TZB		M3	5	6	8	10	12					5	1.3	0.41 - 0.69
SNF-M4-SD-TZB	SNFS-M4-SD	M4		6	8	10	12	16				6	1.3	0.73 - 1.5
SNF-M5-SD-TZB	SNFS-M5-SD	M5			8	10	12	16	20			8	1.8	1.7 - 3.1
SNF-M6-SD-TZB	SNFS-M6-SD	M6				10	12	16	20	25		10	2.3	3.2 - 5.8

**SNF-SD-TZB** Steel - Trivalent Chromate Treatment

Part Number	Qty*1 per pack
SNF-M3-SD-TZB	20
SNF-M4-SD-TZB	20
SNF-M5-SD-TZB	20
SNF-M6-SD-TZB	20

\*1 The minimum order quantity is 1 piece. → P.794

**SNFS-SD** Stainless Steel

Part Number	Qty*1 per pack
SNFS-M4-SD	20
SNFS-M5-SD	20
SNFS-M6-SD	20

\*1 The minimum order quantity is 1 piece. → P.794

Individual Sales → P.794	Cleanroom Wash & Packaging → P.792	Screw Length Adjustment → P.796	Vibration Resistant → P.795	Modification process for captive use → P.791
Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Not Available