



⚠ Precautions for Use

May have lower corrosion resistance than general SUS316L.

We recommend performing a test under the same usage conditions as in actual usage in advance.



- Hardening the screw surface prevents screw seizing / sticking.
- Unlike platings or coatings, there is nothing adhering to the surface, eliminating concerns about contamination due to stripping during tightening.
- Suitable for preventing seizing and sticking in environments where lubricant cannot be used.

● Application

Seizing & Sticking Prevention
FPD production devices / semiconductor production devices / food machinery / general industry machinery

● Material/Finish

RoHS Compliant

	SNSL-PN
Main body	SUS316L Surface hardening treatment
Tensile strength ranking	A4-70

Unit : mm

Part Number	M	L								D1	L1	B	Mass (g)
SNSL-M3-PN	M3	6	8	10	12					5.5	3	2.5	0.71 - 0.96
SNSL-M4-PN	M4		8	10	12	16	20			7	4	3	1.7 - 2.7
SNSL-M5-PN	M5		8	10	12	16	20			8.5	5	4	2.5 - 4
SNSL-M6-PN	M6			10	12	16	20	25	30	10	6	5	4.7 - 8.3
SNSL-M8-PN	M8					16	20	25	30	35	13	8	12 - 19

Part Number	Qty per pack
SNSL-M3-PN	1
SNSL-M4-PN	1
SNSL-M5-PN	1
SNSL-M6-PN	1
SNSL-M8-PN	1

● Part number specification

SNSL - M5 - 16 - PN

Product Code	1	2	Product Code
--------------	---	---	--------------

Individual Sales → P.794	Cleanroom Wash & Packaging → P.792	Screw Length Adjustment → P.796	Vibration Resistant → P.795	Modification process for captive use → P.791
1 unit in 1 bag	Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Please feel free to contact us