




SPS-H Plastic Screw - Hex Head Screws - PPS

WEB Selection Tool
 WEB CAD Download
 Heat-resistance
 Chemical-proof



● Material/Finish

RoHS Compliant

	SPS-H
Main body	PPS (Polyphenylene Sulfide) /Bright Light Brown Glass Fiber 40%
Heat Resistance Temperature*	200°C

*This is the value for the plastic material. The maximum operating temperature of the product changes with performance conditions such as tightening torque.

- PPS has excellent heat resistance and chemical resistance and continuous duty temperature of 200 deg C. Under 200 deg C, no oils, fats, or organic solvents dissolve PPS.
- It has high strength, high rigidity, and high heat resistance strength.
- It has high incombustibility that meets V-0 of UL 94.
- The properties and precautions of plastic screws
➔ P.724

● Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, chemical plants, transformers, electrical and electronic equipment, hot water pumps, and chemical pumps

Unit : mm

Part Number	M	L								B	L1	L2*1	Tension*2 Rupture Load (N)	Torsional*2 Torque (N·m)	Mass (g)	
		1	2	3	4	5	6	7	8							
SPS-M4-H	M4	8	10	12	15	20	25			7	2.8	Full Thread	980	0.71	0.33 - 0.62	
SPS-M5-H	M5	8	10	12	15	20	25	30		8	3.5	Full Thread	1570	1.42	0.54 - 1.1	
SPS-M6-H	M6		10	12	15	20	25	30	40	10	4	Full Thread	2250	2.11	0.96 - 2.1	
SPS-M8-H	M8				15	20	25	30	40	50	13	5.5	27(L=50)	3720	5.29	2.4 - 4.8
SPS-M10-H	M10					20	25	30	40	50	17	7	27(L=50)	5890	11.8	5.1 - 8.3
SPS-M12-H	M12					20	25			19	8	Full Thread	7850	20.6	7.3 - 8	

*1 If the "L" value is other than the value in parentheses, the screw is full thread.

*2 Values in chart are for reference only. They are not guaranteed values. The recommendation torque is 50% of the torsional torque.

Part Number	Qty per pack*1
SPS-M4-H	10
SPS-M5-H	10
SPS-M6-H	10
SPS-M8-H	5
SPS-M10-H	1
SPS-M12-H	1

*1 The minimum order quantity is 1 piece. ➔ P.794

● Part number specification

SPS - M5 - 20 - H

Product Code **1** **2** Product Code

Order in number of packs.

The minimum order quantity is 1 piece. ➔ P.794

Individual Sales ➔ P.794	Cleanroom Wash & Packaging ➔ P.792	Screw Length Adjustment ➔ P.796	Vibration Resistant ➔ P.795	Modification process for captive use ➔ P.791
Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Not Available	Please feel free to contact us