





SPVC-N



SPVC-W



- These products have excellent chemical resistance against strong acids and organic solvents as well as halogen compounds such as hydrogen sulfide and bromine.
- They can be used in atmospheres in which metal and PVC (polyvinyl chloride) cannot be used.
- Max. Operating Temperature** (min./max.):
-10/35 deg C
- Two colors, ivory and gray, are available.

IV ——— Ivory

GR ——— Gray

- The properties and precautions of plastic screws
→ P.724
- Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, and chemical plants

- Material/Finish

	SPVC-N / SPVC-W
Main body	H-PVC(Hard Polyvinyl Chloride)*
Heat Resistance Temperature**	35°C

*Does not comply with the RoHS Directive. These products contain lead.

**This is the value for the plastic material. The maximum operating temperature of the product changes with performance conditions such as tightening torque.

SPVC-N Hex Nuts

Part Number	M	B	T	Mass (g)	Qty per pack
SPVC-M4-N	M4	7	3.2	0.14	1
SPVC-M5-N	M5	8	4.7	0.24	1
SPVC-M6-N	M6	10	5.2	0.44	1

Unit : mm

SPVC-W Washers

Part Number	d	D	t	Nominal	Mass (g)	Qty per pack
SPVC-4-W	4.3	9	0.8	4	0.053	1
SPVC-5-W	5.3	10	1	5	0.077	1
SPVC-6-W	6.4	12.5	1.6	6	0.2	1

Unit : mm

- Part number specification

SPVC-M5-N-IV



Individual Sales → P.794	Cleanroom Wash & Packaging → P.792	Screw Length Adjustment → P.796	Vibration Resistant → P.795	Modification process for captive use → P.791
1 pc. in 1 bag	Available / Add'l charge	Not Available	Not Available	Not Available