



- Full thread socket head cap screws with special low Profile.
- The head height for all screws is 1.5 mm or less.
- Intended for reducing the size of devices and applications with limited overhead space.

● Application

Reducing the size of equipment and devices

● Material/Finish

RoHS Compliant

| | SSHS-FT |
|-----------|---------|
| Main Body | SUS304 |

Unit : mm

| Part Number | M | L | | | | | | | | D1 | L1 | Lb | B | t | Max. Torque (N·m) | Mass (g) |
|-------------|-----|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-------------------|------------|
| SSHS-M3-FT | M3 | 16 | 20 | 25 | 30 | 40 | 50 | | | 6 | 1.3 | 1.5 | 1.5 | 2 | 1 | 0.89 - 2.6 |
| SSHS-M4-FT | M4 | | 20 | 25 | 30 | 40 | 50 | 60 | | 8 | 1.5 | 1.6 | 2 | 2.5 | 2 | 2 - 5 |
| SSHS-M5-FT | M5 | | | | 30 | 40 | 50 | 60 | 70 | 9 | 1.5 | 2 | 3 | 3 | 3.5 | 4.1 - 10 |
| SSHS-M6-FT | M6 | | | | | 40 | 50 | 60 | 70 | 10 | 1.5 | 2.5 | 3 | 4 | 5 | 8.2 - 15 |
| SSHS-M8-FT | M8 | | | | | 40 | 50 | 60 | 70 | 13 | 1.5 | 3 | 4 | 5 | 10 | 14 - 26 |
| SSHS-M10-FT | M10 | | | | | 40 | 50 | 60 | 70 | 16 | 1.5 | 3.5 | 5 | 6 | 18 | 20 - 39 |

| Part Number | Qty per pack |
|-------------|--------------|
| SSHS-M3-FT | 1 |
| SSHS-M4-FT | 1 |
| SSHS-M5-FT | 1 |
| SSHS-M6-FT | 1 |
| SSHS-M8-FT | 1 |
| SSHS-M10-FT | 1 |

● Part number specification

SSHS - M8 - 60 - FT

Product Code **1** **2** Product Code

| | | | | |
|----------------------------|------------------------------------|---------------------------------|-----------------------------|--|
| 1 Individual Sales → P.794 | Cleanroom Wash & Packaging → P.792 | Screw Length Adjustment → P.796 | Vibration Resistant → P.795 | Modification process for captive use → P.791 |
| 1 unit in 1 bag | Available / Add'l charge | Available / Add'l charge | Available / Add'l charge | Available / Add'l charge |