





- Socket head cap screws with special low profile made of pure titanium.
- The head height for all screws is 1.5 mm or less.
- Specific gravity is approximately 60% of stainless steel.
- Useful for space and weight saving of devices.
- Nonmagnetic.
- Excellent chemical and seawater resistance.
- Chemical polishing and brightening processing improve the screw surface. Furthermore, the screws are cleanroom washed, cleanroom packed, and comply with clean specifications that require no oil or foreign matter deposits.
- About the features of titanium → P.625
- Application

Lightweight applications in automobiles, aircrafts, spacecrafts, and robots.

Reducing the size of equipment and devices.
FPD production equipment, semiconductor devices,
electrical and electronic equipment, aquatic applications, and
electrochemical plating

													Unit: mm
Part Number 📶	M	L 1 2				D1	L1	Lb	В	t	Max. Torque (N·m)	Mass (g)	
SSHT-M3	M3	6	8	10			6	1.3	1.5	1.5	2	0.6	0.25 - 0.35
SSHT-M4	M4		8	10	12		8	1.5	1.6	2	2.5	1.2	0.59 - 0.76
SSHT-M5	M5			10	12	16	9	1.5	2	3	3	2.5	0.7 - 1.12
SSHT-M6	M6			10	12	16	10	1.5	2.5	3	4	5	1.1 - 1.7

Part Number	Qty per pack							
SSHT-M3	1							
SSHT-M4	1							
SSHT-M5	1							
SSHT-M6	1							

• Part number specification





