

## Cross Recessed Flat Head Machine Screws with Ventilation Hole




















- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- The flat head does not protrude after tightening.
- Application

Vacuum devices, vacuum chambers, FPD production equipment, semiconductor devices, and electron microscopes

SVFS

## Material/Finish

16

10

12



	Main Body				SUSXM7 (S.S. grade : A2)		
	_						Unit:mm
				D <sub>1</sub>	L1	d	Mass (g)
8				4	1.2	0.8	0.13 - 0.21
8	10			5.2	1.5	1	0.27 - 0.46
8	10	12		6	1.75	1.2	0.49 - 0.77
8	10	12	16	8	2.3	1.5	1 - 1.8
8	10	12	16	10	2.8	1.5	2.2 - 3.1

12

Part Number	Qty*1 per pack
SVFS-M2	10
SVFS-M2.6	10
SVFS-M3	20
SVFS-M4	20
SVFS-M5	10
SVFS-M6	10

4

4

5

5

5

6

6

6

- \*1 The minimum order quantity is 1 piece. → P.794
- Usage example

Part Number 1

SVFS-M2

SVFS-M2.6

SVFS-M3

SVFS-M4 SVFS-M5

SVFS-M6

M

M2

M2.6


МЗ

M4

M5

M6

These screws are effective with vacuum devices and vacuum chambers that require the exhaustion of gas trapped in screw holes.



• Part number specification



Order in number of packs. The minimum order quantity is 1 piece. → P.794

1 Individual Sales → P.794 🕵 Cleanroom Wash & Packaging → P.792 🔐 Screw Length Adjustment → P.796 🖭 Vibration Resistant → P.795 🔐 Modification process for captive use → P.791 Available / Add'l charge | Cleanroom washed and packed | Available / Add'l charge | Not Available Not Available

