



- The ventilation hole helps discharging the gas accumulated at the bottom of the screw holes of machines and devices to support the vacuuming of a vacuum device.
- Cleanroom wash and cleanroom packing are completed. → P.792

#### • Application

Vacuum device / Vacuum container / FPD production device / Semiconductor manufacturing device / Electron microscope

#### • Material/Finish

RoHS Compliant

	SVPS
Main body	SUSXM7 (Equivalent to SUS304)

Unit : mm

Part Number	M	L								D1	L1	d max.	Mass (g)
SVPS-M3	M3	8	10	12	16					5.5	2	1.2	0.61 - 0.94
SVPS-M4	M4		10	12	16	20				7	2.6	1.5	1.3 - 2.1
SVPS-M5	M5			12	16	20	25			9	3.3	1.5	2.7 - 4.2
SVPS-M6	M6			12	16	20	25	30		10.5	3.9	2	4.3 - 7.4
SVPS-M8	M8					20	25	30	35	14	5.2	2	11 - 16

Part Number	Qty per pack*1
SVPS-M3	10
SVPS-M4	10
SVPS-M5	10
SVPS-M6	10
SVPS-M8	10

\*1 The minimum order quantity is 1 piece. → P.794

#### • Related Products

For ventilation of drilled hole, please use **SWAS-VF**.

→ P.574



**SWAS-VF** Washer  
(with Ventilation Groove)

#### • Part number specification

**SVPS-M4-12**



Order in number of packs.

The minimum order quantity is 1 piece. → P.794

Individual Sales → P.794	Cleanroom Wash & Packaging → P.792	Screw Length Adjustment → P.796	Vibration Resistant → P.795	Modification process for captive use → P.791
Available / Add'l charge	Cleanroom washed and packed	Available / Add'l charge	Not Available	Please feel free to contact us