



SWUT Hex Lock Nuts - Titanium

WEB Selection Tool


WEB CAD Download

Cleanroom wash & packaging

Non-Magnetic

Lightweight

Vibration resistant treatment



- Specific gravity is approximately 60% of stainless steel.
- These nuts are equipped with vibration resistant patch to prevent screw from loosening.
- Continuous Max. Operating Temperature :
-40 to 120 deg C

● Application

Lightweight applications in automobiles, aircrafts, spacecrafts, and robots
FPD production equipment, semiconductor devices, electrical and electronic equipment, and loosening prevention

● Material/Finish

RoHS Compliant

| | SWUT |
|------------|--------------------------------|
| Main Body | FRS-9901 (Equivalent to TW340) |
| Nylon Ring | Nylon 66 |

Unit : mm

| Part Number | M | B | C (Approx.) | T | Mass (g) | Qty per pack |
|-------------|-----|-----|-------------|-----|----------|--------------|
| SWUT-M3 | M3 | 5.5 | 6.4 | 4 | 0.27 | 1 |
| SWUT-M4 | M4 | 7 | 8.1 | 5 | 0.52 | 1 |
| SWUT-M5 | M5 | 8 | 9.2 | 6.5 | 0.77 | 1 |
| SWUT-M6 | M6 | 10 | 11.5 | 8 | 1.8 | 1 |
| SWUT-M8 | M8 | 13 | 15 | 9.8 | 3.5 | 1 |
| SWUT-M10 | M10 | 17 | 19.6 | 12 | 7.3 | 1 |

● Related Products

SWUS Hexagon Lock Nut made of stainless steel is available.

→ P.782



● Part number specification

SWUT-M6

1

| | | | | |
|--------------------------|------------------------------------|---------------------------------|-----------------------------|--|
| Individual Sales → P.794 | Cleanroom Wash & Packaging → P.792 | Screw Length Adjustment → P.796 | Vibration Resistant → P.795 | Modification process for captive use → P.791 |
| 1 pc. in 1 bag | Cleanroom washed and packed | Not Available | Not Available | Not Available |