



FOOT SWITCHES TOUCH PADS

■ Foot Switches

Model	Operating force (under 90° pressing plate) and weight	Applications and features
<p>OT-112 (black)</p> <p>(W) 135× (D) 55× (H) 15.5</p>	<p>107 N (approx.)</p> <p>230 g (approx.)</p>	<ul style="list-style-type: none"> ● External sheathing: NBR (oil-resisting rubber) ● Applications: for operation of medical equipment, general small-size industrial equipment, and sewing equipment ● Drip-proof ● Flexible and durable, resistant to stomping and jumping ● a-contact (momentary type) ● Lead wire: included (S-VCTF; 0.75 mm², 2-strand, 2 m) ● Mounting: with 2-M4 or double-sided tape, etc. ● Rated voltage/current: 28 V AC/DC, 1 A

■ Touch Pads

Model	Operating force (under 90° pressing plate) and weight	Applications and features
<p>OT-TP-2 (black)</p> <p>(W) 50× (D) 50× (H) 10</p>	<p>28 N (approx.)</p> <p>24 g (approx.)</p>	<ul style="list-style-type: none"> ● External sheathing: PVC (polyvinyl chloride) ● a-contact (momentary type) ● Lead wire: included (24 AWG, 2-strand, 480 mm) ● Mounting: with double-sided tape, adhesive, etc. ● ※Electrical ratings: Use 28 V AC or DC, 0.3 A or less for safety. <p>(produced by Tapeswitch Corporation)</p>
<p>OT-NO-1 (black)</p> <p>(φ) 37× (H) 5.5</p>	<p>17 N (approx.)</p> <p>7 g (approx.)</p>	<ul style="list-style-type: none"> ● External sheathing: PVC (polyvinyl chloride) ● Applications: wide-ranging; e.g., for detection in an area with a limited mounting space, for transmission of a signal in response to release (lifting) of an object. ● Thin, water-tight ● a-contact (momentary type) ● Lead wire: included (24 AWG, 2-strand, 480 mm) ● Mounting: with double-sided tape, adhesive, etc. ● ※Electrical ratings: Use 28 V AC or DC, 0.3 A or less for safety. <p>(produced by Tapeswitch Corporation)</p>
<p>OT-NO-2 (black)</p> <p>(W) 27.5× (D) 22× (H) 5.5</p>	<p>11 N (approx.)</p> <p>7 g (approx.)</p>	<ul style="list-style-type: none"> ● External sheathing: PVC (polyvinyl chloride) ● Applications: wide-ranging; e.g., for detection in an area with a limited mounting space, for transmission of a signal in response to release (lifting) of an object. ● Thin, water-tight ● a-contact (momentary type) ● Lead wire: included (24 AWG, 2-strand, 480 mm) ● Mounting: with double-sided tape, adhesive, etc. ● ※Electrical ratings: Use 28 V AC or DC, 0.3 A or less for safety. <p>(produced by Tapeswitch Corporation)</p>