





Connector type-for read/ write head

Type	Straight	Angle	Straight	Angle
				
	P10254	P10253	P10159	P10160

Type	BIS C-518-PVC-__	BIS C-517-PVC-__	BIS C-505-PU-__	BIS C-506-PU-__
Applicable R/W head	BIS C-315 / __-S4 BIS C-319 / __-S4 BIS C-323 / __-S4 BIS C-324 / __-S4 BIS C-325 / __-S4	BIS C-315 / __-S4 BIS C-319 / __-S4 BIS C-323 / __-S4 BIS C-324 / __-S4 BIS C-325 / __-S4	BIS C-315 / __-S4 BIS C-319 / __-S4 BIS C-323 / __-S4 BIS C-324 / __-S4 BIS C-325 / __-S4	BIS C-315 / __-S4 BIS C-319 / __-S4 BIS C-323 / __-S4 BIS C-324 / __-S4 BIS C-325 / __-S4
cable material	PVC	PVC	PUR	PUR
Remarks				

Please specify the type number as shown below;

BIS C-518-PVC-05

cable length¹⁾

01=1m
05=5m
10=10m²⁾

- 1) The cable length should be the same as the length shown in the type number of a read/write head. Cables on read/write heads must not be shortened, since functionality can then no longer be ensured
- 2) At 10m cable length, read/write distance is reduced by 10%.